

SECTION 1 – IDENTIFICATION

PRODUCT IDENTIFIER Cryotech Glacier RTU® Lavatory Antifreeze

OTHER MEANS OF IDENTIFICATION

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

Premixed low-temperature lavatory fluid containing antifreeze, deodorant, and colorant in ready-to-use formulation

RESPONSIBLE PARTY INFORMATION

Name/Address	Cryotech Deicing Technology 6103 Orthoway Fort Madison, IA 52627
	United States
Contact information	Telephone: (800) 346-7237
	Email: <u>deicers@cryotech.com</u>
	Website: <u>www.cryotech.com</u>
EMERGENCY PHONE NUMBER	CHEMTREC: (800) 424-9300
	Outside USA and Canada: (703) 741-5970

SECTION 2 – HAZARD IDENTIFICATION

HAZARD INFORMATION ACCORDING TO OSHA HAZCOM 2024

Hazard classification	Not classified as hazardous
Signal word	N/A
Hazard statement(s)	N/A
Hazard symbol(s)	No pictogram
Precautionary statement(s)	Not required
Hazards not otherwise classified	None

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURES

Chemical Name	Common name and synonyms	CAS number	%(wt.)
Propane-1,2-diol	Propylene glycol	57-55-6	30-60
Water		7732-18-5	45-70
Trade secret/proprietary corrosion inhibitors, fragrance, and colorant in amounts <1%			



SECTION 4 – FIRST AID MEASURES

DESCRIPTION OF FIR	ST AID MEASURE
Inhalation	If inhaled, remove to fresh air. Get medical advice if cough or other symptoms appear.
Skin	Wash hands and exposed skin thoroughly after handling.
Еуе	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	If swallowed, give milk or water to drink and telephone for medical advice. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

May cause temporary minor eye irritation. Symptoms may include discomfort or pain, excess blinking, and tear production, with possible redness and swelling. Inhalation of mist during handling may cause minor respiratory tract irritation and coughing.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

If you feel unwell, seek medical advice. Treat symptomatically.

SECTION 5 – FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA

Water, carbon dioxide, or dry chemical. Use extinguishing media appropriate for the surrounding environment.

UNSUITABLE EXTINGUISHING MEDIA

Not applicable

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Heat from fire can generate flammable vapor. Vapor is heavier than air and may spread along floors. Pressure buildup in sealed containers in high heat conditions may cause container to rupture.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Wear protective equipment suitable for the surrounding environment.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Avoid eye/skin contact with spilled material. Wear appropriate personal protective equipment (refer to Section 8 of this SDS).

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Contain and/or absorb spill with inert material (e.g., sawdust, sand, kitty litter). Scoop up material and transfer to disposal container. Mop area with water while containing the spread of the material to control staining.

SECTION 7 – HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Avoid eye/skin contact. Avoid breathing of mist. Wear appropriate personal protective equipment (refer to Section 8 of this SDS). Wash hands thoroughly after use. Change contaminated clothing.

PRECAUTIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Store in tightly sealed containers, away from direct heat and strong oxidizing agents. Store above -7°F (-21°C).



SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

US OSHA PERMISSIBLE EXPOSURE LIMIT (PEL)

No specific limits established.

AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS THRESHOLD LIMIT VALUE (TLV)

No TLV established.

AMERICAN INDUSTRIAL HYGIENE ASSOCIATION (AIHA)

Workplace Environmental Exposure Level (WEEL) for Propane-1,2-diol (CAS: 57-55-6): 8-hr Time-weighted Average (TWA): 10 mg/m³

APPROPRIATE ENGINEERING CONTROLS

Have eyewash stations available. Ensure adequate ventilation if handling in confined areas.

INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT

Wear safety glasses with side shields or safety goggles. Clothing should be suitable to protect skin (e.g., long sleeves, long pants). Avoid breathing mist. If conditions create high airborne concentrations of this product, use an approved respirator, such as an N95 mask. Always use good personal hygiene habits when using this product, such as avoiding touching the face, and thoroughly and regularly washing hands.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Color	Blue
Odor	Floral (Odor threshold not available)
Melting point/freezing point	< -7°F (-21°C)
Boiling point	~ 221°F (105°C)
Flammability	Not flammable
Explosive limits (lower and upper)	Data not available
Flash point	> 219°F (104°C) based on propylene glycol
Auto-ignition temperature	> 752°F (400°C) based on propylene glycol
Decomposition temperature	Data not available
рН	5-9
Kinematic viscosity	<5 cP at 20°C
Solubility	Completely miscible in water
Partition coefficient n-octanol/water	Data not available
Vapor pressure	Data not available
Relative density	1.02-1.05
Relative vapor density	Data not available
Particle characteristics	Not applicable
SECTION 10 - STABILITY AND REACTL	

SECTION 10 – STABILITY AND REACTIVITY

REACTIVITY

This product is expected to be non-reactive under normal conditions of use, storage, and transport.

CHEMICAL STABILITY

Stable. Polymerization will not occur.

POSSIBILITY OF HAZARDOUS REACTIONS, INCLUDING THOSE ASSOCIATED WITH FORESEEABLE EMERGENCIES

No dangerous reactions known under conditions of normal use.

CONDITIONS TO AVOID

Avoid prolonged exposure to temperatures over the boiling point of water. When water has evaporated, remaining material is combustible.

Prepared according to the US OSHA Hazard Communication Standard (29 CFR 1910.1200) Cryotech Deicing Technology, 6103 Orthoway, Fort Madison, IA 52627 Form# MKT2102 Rev. August 1, 2024



INCOMPATIBLE MATERIALS

Strong oxidizing agents; strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS

May decompose into oxides of carbon (e.g., CO, CO₂).

SECTION 11 – TOXICOLOGICAL INFORMATION

INFORMATION ON LIKELY ROUTES OF EXPOSURE

Ingestion is unlikely during normal operations. Inhalation of material is most likely when in confined areas. Skin contact may occur from mixing operations. Eye contact is possible from touching eyes with contaminated hands.

SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL, AND TOXICOLOGICAL CHARACTERISTICS

May cause minor temporary eye irritation. Corneal injury is unlikely. Inhalation of material during handling may cause temporary respiratory tract irritation and coughing. Repeated contact may cause minor skin irritation. Not expected to cause significant health effects by accidental ingestion.

DELAYED AND IMMEDIATE EFFECTS AND CHRONIC EFFECTS FROM SHORT- AND LONG-TERM EXPOSURE

This product is not expected to produce serious delayed or chronic effects from short- or long-term exposure.

NUMERICAL MEASURES OF TOXICITY

LD50 rat-oral: > 15 g/kg (estimated from studies of components)

INTERACTIVE EFFECTS

None known.

CARCINOGENIC INFORMATION

No component in this product is listed in the National Toxicology Program (NTP) Report on Carcinogens or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs or by OSHA.

SECTION 12 – ECOLOGICAL INFORMATION

ECOTOXICITY

Not expected to cause long-term adverse effects in the aquatic or terrestrial environments.

PERSISTENCE AND DEGRADABILITY

Biodegradable. COD (TOD): 0.71 g O2/g deicer; BOD5 (20°C): 0.25 g O2/g product

BIOACCUMULATIVE POTENTIAL

Data not available

MOBILITY IN SOIL Data not available

OTHER ADVERSE EFFECTS

None expected.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE RESIDUES AND INFORMATION ON SAFE HANDLING AND METHODS OF DISPOSAL

Based on available information, this product is neither listed as a hazardous waste nor does it exhibit any of the characteristics that would cause it to be classified as a characterized hazardous waste under the US Resource Conservation and Recovery Act (RCRA). If recovered product is not fit for use, dispose of contents/container in accordance with local, state, regional, national, and/or international regulations.

Prepared according to the US OSHA Hazard Communication Standard (29 CFR 1910.1200) Cryotech Deicing Technology, 6103 Orthoway, Fort Madison, IA 52627 Form# MKT2102 Rev. August 1, 2024



SECTION 14 – TRANSPORT INFORMATION

UN number UN proper shipping name Transport hazard class(es) Packing group Environmental hazards Transport in bulk Special precautions Not applicable. This material is not regulated as dangerous per US DOT or IATA/ICAO. Not applicable Not applicable Not applicable Not applicable. This material is not a Marine pollutant. Consult IMO regulations before transporting ocean bulk. Not applicable

SECTION 15 – REGULATORY INFORMATION

INVENTORY LISTS

All of the components in this product are on the following inventory lists: US (TSCA), Canada (DSL/NDSL), Europe (EINECS); or not required to be listed.

TSCA SECTION 12(B)

None of the chemicals in this product are listed under US EPA Toxic Substances Control Act (TSCA) Section 12(b).

CERCLA HAZARDOUS SUBSTANCES

This material, as supplied, does not contain any chemicals regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302). There is no CERCLA Reportable Quantity for this material. There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT (EPCRA) SECTION 313

None of the chemicals in the product are subject to reporting under the US EPA Toxics Release Inventory (TRI) program.

Health hazard	
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Aspiration hazard	No
Reproductive toxicity	No
Germ cell mutagenicity	No
Skin corrosion or irritation	No
Respiratory or skin sensitization	No
Serious eye damage or eye irritation	No
Specific organ toxicity (single or repeated exposure)	No
Simple asphyxiant	No
Hazard not otherwise classified (HNOC)	No

HAZARD CATEGORIES FOR EPCRA 311 / 312
Health hazard


Physical hazard	
Flammable (gases, aerosols, liquids or solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (liquid or solid)	No
Pyrophoric gas	No
Oxidizer (liquid, solid or gas)	No
Organic peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible dust	No
Corrosive to metal	No
Hazard not otherwise classified (HNOC)	No

CLEAN WATER ACT

None of the chemicals in this product are listed as Priority Pollutants under the US EPA CWA. None of the chemicals in this product are listed as Toxic Pollutants under the US EPA CWA.



NFPA 704



SECTION 16 – OTHER INFORMATION

SDS REVISION DATE

This SDS was revised on August 1, 2024.

The latest version can be obtained by contacting Cryotech Deicing Technology.

DISCLAIMER

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use or misuse are beyond our control, GENERAL ATOMICS INTERNATIONAL SERVICES CORPORATION dba Cryotech Deicing Technology makes no warranty, either express or implied, with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. GENERAL ATOMICS INTERNATIONAL SERVICES CORPORATION SERVICES CORPORATION dba Cryotech Deicing Technology assumes no responsibility for any injury or loss resulting from the use of the product described herein. User should satisfy himself that he has all current data relevant to his particular use.

End of Safety Data Sheet